

Webasto Thermoduct



Webasto Thermoduct is constructed using Thinsulate™, the Market Leader in Thermal Insulation Material.

The material is stitched into 750mm long tubes and is designed to slide directly over warm air ducting, providing exceptional thermal insulating properties.

Available for 60mm, 80mm, 100mm and 150mm ducting sizes.

Features & Benefits

- Temperature Resistant up to 140°C
- Hydrophobic—actually repels water, thus preventing mould and mildew
- Hypoallergenic
- Easy to handle
- Can double the effective heat output from air heaters by minimising ducting heat loss
- Allows long ducting runs to provide effective heat output
- Reduces heater running times, improving fuel and electrical power consumption
- Reduces external duct temperature from circ. 100°C to 30°C

| Webasto Part Number | Description |
|---------------------|---------------------------------------|
| 41S70014A | 60mm Webasto Thermoduct—750mm length |
| 41S70015A | 80mm Webasto Thermoduct—750mm length |
| 41S70016A | 100mm Webasto Thermoduct—750mm length |
| 41S70017A | 150mm Webasto Thermoduct—750mm length |

Typical Applications

- All Air Heating Systems
- All Ducted Air Conditioning Systems

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67